



BT5

BATTERY TESTER

BATTERY TEST SIZE :

AAA @ 10mA LOAD
AA @ 50mA LOAD
D @ 250mA LOAD

PHOTO BATTERY TEST :

1.5V , 3V , 6V

BUTTON BATTERY TEST :

1.2 , 1.5V @ 1mA

BATTERY PACKS :

4.5V , 6V , 9V , 12V , 22V



YX1000

ANALOGUE MULTI METER

DCV	0- 2.5 -10-50-250-500 VOLT	3 % FSD
ACV	0 - 10 - 50 - 250 - 500 VOLT	5 % FSD
DCA	0 - 500u - 10mA - 250 Ma	3 % FSD
OHM	R X 10 , R X 1K	3 % FSD
SIZE	95 X 60 X 33 mm	
WEIGHT	80g	
BATTERY	"AA" 1.5V X 1	



YX2000A

ANALOGUE MULTI METER

DCV	0- 2.5 -10-50-250-500 VOLT	3 % FSD
ACV	0 - 10 - 50 - 250 - 500 VOLT	5 % FSD
DCA	0 - 500u - 10mA - 250 Ma	3 % FSD
OHM	R X 10 , R X 1K	3 % FSD
BATT	1.5V , 9V	
SIZE	105 X 70 X 33 mm	
WEIGHT	85g	
BATTERY	"AA" 1.5V X 1	



YX-360TRN

ANALOGUE MULTI METER

DCV	0.1 - 0.5 - 2.5 - 10 - 50 - 250 - 1000 VOLT 20Kohm / V +3% FSD
ACV	10 - 50 - 250 - 1000 V : 9K ohm / V 4% FSD
DCA	50u - 2.5m - 25m - 250m , 3% FSD
OHM	2K - 20K - 200K - 2M , 3% of arc
Db	-10 , 62dB
	FUSE & DIODE PROTECTION
SIZE	150 X 100 X 36 mm
WEIGHT	280G
POWER	2 X 1.5V , 1 X 9V BATTERIES



DT-830B

DIGITAL MULTI METER

DCV	200m - 2 - 20 - 200 - 1000 V	0.8%
ACV	200 - 750 VOLT	1.5%
DCA	200u - 2m - 20m - 200m - 10 A	1.0%
OHM	200 - 2K - 20K - 200K - 2M ohm	1.0%
DIODE	3V / 0.8mA	

3 1/2 DIGITS LCD , MAX READING OF 1999

OVERLOAD PROTECTION

LOW BATTERY INDICATION

TRANSISTOR TESTER

SIZE 126 X 70 X 28

POWER 1 X 9V



DT-830D

DIGITAL MULTI METER

DCV	200m - 2 - 20 - 200 - 1000 V	0.8%
ACV	200 - 750 VOLT	1.5%
DCA	200u - 2m - 20m - 200m - 10 A	1.0%
OHM	200 - 2K - 20K - 200K - 2M ohm	1.0%
DIODE	3V / 0.8mA	

3 1/2 DIGITS LCD , MAX READING OF 1999

OVERLOAD PROTECTION

LOW BATTERY INDICATION

CONTINUITY BUZZER

SIZE 126 X 70 X 28

POWER 1 X 9V



M300

POCKET SIZE DIGITAL MULTI METER

Voltage DC:2/20/200/500V

Voltage AC:200/500V

Current DC:200mA

Resistance:2k/20k/200k/2000kΩ

Diode Check:3.2V/1mA

·Audible continuity

·Low battery indication

·Overload protection

Power:12V battery (23A)

Dimensions(WxLxT):75x120x18 mm

Weight:110g (with battery)



UT-30D

DIGITAL MULTI METER

DCV	200m - 2 - 20 - 200 - 500 V	0.5%
ACV	200 - 500 VOLT	1.0%
DCA	200u - 2m - 20m - 200m Amp	1.2%
OHM	200 - 2K - 20K - 200K - 2M ohm	1.0%
DIODE	2.8V / 1mA	
HFE	Vce 3V , 10uA	
SIGNAL	50Hz Square wave	
CONTINUITY BUZZER		
HOLD BUTTON		
SIZE	138 x 69 x 31 mm	
POWER	1 X 9V	
3 1/2 DIGITS LCD , MAX READING OF 1999		



DMM-8902

HIGH PRECISION DIGITAL MULTI METER WITH RUBBER HOLDER

DCV	200m - 2 - 20 - 200 - 1000 V	0.5%
ACV	200m - 2 - 20 - 200 - 750 V	0.8%
DCA	200u - 2m - 20m - 200m - 10 Amp	0.8%
ACA	200u - 2m - 20m - 10A	1.2%
OHM	200 - 2K - 20K - 200K - 2M - 20M - 200M OHM	
DIODE	2.8V / 1mA	
HFE	Vce 3V , 10uA	
3 1/2 DIGITS LCD , MAX READING OF 2000		
SIZE	178 X 85 X 35 mm	
POWER	1 X 9V ,	



MY64

HIGH PRECISION DIGITAL MULTI METER

DCV	200m - 2 - 20 - 200 - 1000 V	
ACV	200m - 2 - 20 - 200 - 750 V	
DCA	200u - 2m - 20m - 200m - 10 Amp	
ACA	200u - 2m - 20m - 10A	
OHM	200 - 2K - 20K - 200K - 2M - 20M - 200M	
CAP	2nF - 20nF - 200nF - 2uF - 20 Uf	
TEMP	-40°C - 1400°C	
FREQ	20K Hz	
DIODE	2.8V / 1mA	
HFE	Vce 3V , 10uA	
3 1/2 DIGITS LCD , MAX READING OF 2000		
SIZE	178 X 85 X 35 mm	
POWER	1 X 9V , AUTO OFF	



EM6013B

CAPACITANCE METER

CAP RANGE :

2000pF - 20NnF - 200nF - 2uF - 20uF

200Uf - 2000uF - 20mF - 200mF

SIZE : 190 X 92 X 28 mm

EH92 = YELLOW HOLSTER



EM382B

HIGH PRECISION DIGITAL MULTI METER

·3 1/2 digits LCD,Max.reading of 1999

Voltage DC:200m/2000m/20/200/600V

Voltage AC:200/600V

Current DC:200μ/2000μ/20m/200m/10A

Resistance:200/2000/20k/200k/2000kΩ

Battery Check:1.5V, 9V, 12V

Diode Check:2.8V/1mA

Continuity: <30Ω , Audible continuity

Low battery indication

Overload protection

Power:9V battery (6F22)

Dimensions(WxLxT):74x137x32 mm

Weight:160g (with battery)



EM382C

HIGH PRECISION DIGITAL MULTI METER

·3 1/2 digits LCD,Max.reading of 1999

Voltage DC:200m/2000m/20/200/600V

Voltage AC:200/600V

Current DC:200μ/2000μ/20m/200m/10A

Resistance:200/2000/20k/200k/2000kΩ

Diode Check:2.8V/1mA

Continuity: <30Ω , Audible continuity

Temperature:0~1000°C

Low battery indication

Overload protection

Power:9V battery (6F22)

Dimensions(WxLxT):74x137x32 mm

Weight:160g (with battery)

EM416

NETWORK CABLE TESTER



EM416

EM412

- Testing for open ,short and miswire, reversals
- Shield detection :test a cable shield Integrity
- Main unit and one remote allow one person to test
- TIA/EIA568A,568B,10base-T,Token Ring
- Low battery indicator

DT266

DIGITAL CLAMP MULTI METER



DCV	200m - 20 - 1000 V	0.8%
ACV	200m - 20 - 750 V	1.2%
ACA	20 - 200 - 1000A	2.5%
OHM	2000 - 20K Ohm	1.0%
FREQ	20M Hz	1.5%
TEMP	,-40oC - 750oC	3.0%
CONTINUITY BUZZER		
3 1/2 DIGITS LCD , MAX READING OF 1999		
OVERLOAD PROTECTION		
LOW BATTERY INDICATION		
DATA HOLD BUTTON		
SIZE	230 X 70 X 37mm	
POWER	1 X 9V	

ETP101

3 IN 1 THERMO-HYGROMETER & CLOCK



- Current time and date display
- Time alarm function
- 12/24 hours clock
- °C/°F temperature
- Relative humidity and relevant comfort degree
- Real time indications of temperature and humidity fluctuation

This unit can display current time and date, and determine whether the environment is comfortable, too wet or too dry. Alarm function, temperature unit selection, storage of Max.and Min.. Temperature and humidity values are available. It is very useful and easy to use.



TS99

**LASER DISTANCE METER
BEAM DETECTOR**

VOLTAGE DETECTOR

METAL DETECTOR

ULTRASONIC AND LASER TECHNOLOGY

LCD DISPLAY AND BEEP SOUND

DISTANCE : 0.4 TO 18mtrs +- 0.5%

METAL DETECTOR - UP TO 30mm - COPPER

- UP TO 75mm STEEL

WOOD STUD DETECTOR - UP TO 30mm

220V AC DETECTOR - UP TO 50mm

WORKING TEMPERATURE : -7°C TO 40°C

9V BATTERY

**CALCULATE AREA AND VOLUME
METRIC AND IMPERIAL SYSTEM**



TS73

METAL / VOLTAGE DETECTOR

3 IN 1 SUPER DETECTOR

LED OR BEEP SOUND

METAL DETECTOR - UP TO 25mm

220V AC DETECTOR - UP TO 40mm

STUD / NAIL DETECTOR - UP TO 20mm

WORKING TEMPERATURE : -20°C TO 60°C

9V BATTERY



TS75

METAL / VOLTAGE DETECTOR

2 IN 1 SUPER DETECTOR

LED OR BEEP SOUND

METAL DETECTOR - UP TO 25mm

220V AC DETECTOR - UP TO 40mm

WORKING TEMPERATURE : -20°C TO 60°C

9V BATTERY



GK-1

MULTI TEST PROBE

AC TEST PROBE

BATT 1.5V X 2

LENGTH 136mm



DT261

ISOLATION TESTER FOR DT266

RATED VOLTAGE : 500V DC

OHM : 20M OHM +2% , 2000M OHM +5%

DIMENSIONS : 90 X 70 X 35 mm



PANEL METER

DC VOLT METER

RANGE: DCV 200mV / 2V / 20V / 200V / 500V

3 1/2 DIGITS

MAX READING 1999

ACCURACY \pm 0.5%

POWER : 8 - 12V DC

SIZE : 72 X 46.5 X 28mm