



## HSR108-8T

### CEILING SPEAKER 8" 40 WATT 100V LINE

10, 20, 40 Watt max / 100v line  
8" woofer with coaxial tweeter  
Frequency range: 100Hz-20kHz  
Sensitivity : 92dB /1W/1m  
ABS housing, Metal grill  
Dimension : ØD 255 x 75 mm  
Mounting hole: Ø218mm  
Quick fit 4 post screw mounting



## HSR108-6T

### CEILING SPEAKER 6" 10WATT 100V LINE

2.5, 5, 10 watt 100V line  
6 1/2" woofer with co-axial tweeter  
Frequency range: 150Hz-16kHz  
Sensitivity: 92dB/1W, 1m  
ABS housing, Metal grill  
Quick fit 4 post screw mounting  
Dimension: Ø230x75mm  
Mounting hole: Ø186mm  
Approx. 1.0kg



## HST153-6T

### CEILING SPEAKER 6 1/2" 5WATT 100V LINE - SHALLOW TYPE

5, 2.5, 1.25 WATT 100V LINE  
SPEAKER : 6 1/2" 8 OHM  
Frequency range: 150Hz-15kHz  
All metal  
Dimension : ØD 210 x 57 mm  
Mounting hole: Ø165mm  
Sensitivity : 92dB /1W/1m  
Quick fit spring mounting



## HSR151-5T

### 5" 8 OHM SPEAKER 5WATT 100V LINE

1.3/2.5/5 watts RMS Power 100V LINE  
ABS housing, Metal grill  
Sensitivity: 90dB/1W, 1m  
Frequency range: 130Hz-17kHz  
Dimension: 222x222x65mm  
Mounting hole: 171x171mm  
Quick fit, 4 post screw type