



HI 2050

Audio mixing, recording studio monitoring
Home entertainment , theatre

FEATURES

- Full-bodied bass, well-balanced mids and highs
- Adjustable headband for different head shape
- Exquisite and durable aluminium structure
- Soft velour ear pads for comfortable wearing
- Stylish stainless steel ear cup design

SPECIFICATION

- Type: Wired, open design
- Transducer Principle: Dynamic
- Wearing Style: Head worn
- Frequency Response: 15Hz-25kHz
- Sensitivity: 92dB±3dB
- Driver Diameter: Ø53mm
- Max.Input Power: 500mW
- Rated Power: 250mW
- Impedance: 60Ω
- Connector: stereo Ø3.5mm + Ø6.3mm gold plated
- Cable: Ø4mm x 2.2m + 1.8m extension cable , OFC
- Net Weight: 325g



HD 2000

Audio mixing, recording studio monitoring ,
Hi-Fi sound

FEATURES

- Soft, high protein leather ear pads for comfortable wearing
- Swivel ear cup design for 25° right or left swivel for different face shape,
- 180° outward swivel for single hand monitoring
- Adjustable headband allows you to extend or shorten the length by 35mm

SPECIFICATION

- Type: Wired, closed design
- Transducer Principle: Dynamic
- Wearing Style: Head worn
- Frequency Response: 10Hz-25kHz
- Sensitivity: 101dB±3dB at 1kHz
- Driver Diameter: Ø50mm
- Max.Input Power: 100mW
- Rated Power: 30mW
- Impedance: 32Ω
- Connector: stereo Ø3.5mm + Ø6.3 gold plated
- Cable: Ø2.2mm x 2m, Y-type
- Net Weight: 200g



TS 511

Audio mixing, recording studio monitoring ,
Hi-Fi sound

FEATURES

- Crystal clear sound with the low self-noise
- Its trendy style, self-adjusting headband as well as the moderate weight design ensures comfort in use .

SPECIFICATION

- Type: Dynamic
- Driver Diameter: Ø57mm
- Impedance: 64Ω
- Sensitivity: 102dB
- Frequency Response: 20Hz-20kHz
- Power Handling Capability: 1000mW
- Cable: Approx. 3m
- Adaptor Plug: Stereo Ø3.5mm + Ø6.3mm



TS-670

STUDIO MONITOR HEADPHONE

Audio mixing, recording studio monitoring , Home
entertainment , theatre

FEATURES

- Soft skin ear pads for excellent ambient noise attenuation
- Light headband for wearing comfort
- Smooth, natural sound and high sensitivity
- Wide dynamic range and high sound quality meet the demands of recording monitoring

SPECIFICATION

- FREQUENCY RESPONSE : 20Hz -20KHz
- IMPEDANCE : 45 Ohm
- SENSITIVITY : 98dB
- MAX INPUT POWER : 2000mW
- SPEAKER DIMENSION : 50mm OD
- CABLE :1.2 TO 4 METERS STRETCH CABLE
- PLUG : 3.5mm STEREO GOLD PLUG
- ADAPTOR : 3.5mm TO 6.3mm GOLD
- 20 PCS / CTN



TS-600

DJ, audio mixing, recording studio monitoring

FEATURES

- Adjustable headband
- 90°swiveling earcup
- Featuring natural mids and smooth highs
- Soft skin ear pads for excellent ambient noise attenuation
- Plug-in cable for easy cable replacement

SPECIFICATION

- Transducer Principle: Dynamic
- Driver Diameter: Ø50mm
- Impedance: 32Ω
- Sensitivity: 102dB
- Frequency Response: 20Hz-20kHz
- Power Handling Capability: 1500mW
- Cable: Ø4mm x 1.2m Spring Cable (full stretch length approx. 4m)
- Adaptor Plug: Stereo Ø3.5mm + Ø6.3mm

20 PCS / CTN



TS-819

Audio mixing , Hi-Fi , Home entertainment

FEATURES

- Crystal clear sound with the low self-noise , good bass
- Self-adjusting headband as well as the moderate weight design ensures comfort in use .

SPECIFICATION

DYNAMIC HIFI HEADPHONE

FREQUENCY RESPONSE : 20Hz -20KHz

IMPEDANCE : 32 Ohm

SENSITIVITY : 102dB

INLINE VOLUME CONTROL

MAX INPUT POWER : 200mW

SPEAKER DIMENSION : 40mm OD

CABLE : 4 METERS

PLUG : 3.5mm STEREO GOLD PLUG

ADAPTOR : 3.5mm TO 6.3mm GOLD

20 PCS / CTN



TS-368

DYNAMIC HIFI HEADPHONE

FREQUENCY RESPONSE : 20Hz -20KHz

IMPEDANCE : 32 Ohm

SENSITIVITY : 102dB

MAX INPUT POWER : 150mW

SPEAKER DIMENSION : 40mm OD

INLINE VOLUME CONTROL

CABLE : 4 METERS

PLUG : 3.5mm STEREO GOLD PLUG

ADAPTOR : 3.5mm TO 6.3mm GOLD

20 PCS / CTN



TS-422

DYNAMIC HIFI HEADPHONE WITH VOLUME CONTROL

FREQUENCY RESPONSE : 20Hz -20KHz

IMPEDANCE : 32 Ohm

SENSITIVITY : 102dB

MAX INPUT POWER : 80mW

INLINE VOLUME CONTROL

SPEAKER DIMENSION : 40mm OD

CABLE : 3 METERS

PLUG : 3.5mm STEREO GOLD PLUG

ADAPTOR : 3.5mm TO 6.3mm GOLD

30 PCS / CARTON



TS-828

DYNAMIC HIFI HEADPHONE

FREQUENCY RESPONSE : 20Hz -20KHz

IMPEDANCE : 32 Ohm

SENSITIVITY : 102dB

MAX INPUT POWER : 150mW

SPEAKER DIMENSION : 40mm OD

CABLE : 2 METERS

PLUG : 3.5mm STEREO GOLD PLUG

ADAPTOR : 3.5mm TO 6.3mm

BLISTER PACK

30 PCS / CARTON

